



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality,
hereby attests that the product(s):

STEEL STRAND, UNCOATED SEVEN-WIRE FOR PRESTRESSED CONCRETE

(Details as per the attached Scope of Certification)

manufactured by:

GULF STEEL STRANDS FZE
Jebel Ali Free Zone, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

ASTM A 416/A 416 M -10

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark to the above-mentioned product(s).

ENGR. HAWWA ABDOULLA BASTAKI
Director, Dubai Central Laboratory Department
Dubai Municipality

Certificate No: CL09020100
Valid Until: 06 April 2012

Current Issue Date: 07 April 2011
Original Issue Date: 07 April 2009



The attached Scope of Certification bearing the same Certificate No. forms an integral part of this certificate.
This certificate is subject to the Terms and Conditions of the Product Certification System

CB-003



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL09020100**

Certificate Issued To: Gulf Steel Strands F.Z.E
Jebel Ali Free Zone, P.O.BOX 262144
Dubai, UAE.

Applicable Standard Specification: ASTM A 416/A 416 M - 10 Specification for Steel Strand, Uncoated Seven Wire for Prestressed Concrete

Applicable Specific Rules: RD-DP21-2131 (IC) "Specific Rules for Certification of Steel Strand, Uncoated Seven Wire for Prestressed Concrete (as per ASTM A 416/A 416 M - 10) Through Factory Assessment".

S/N	Product Description	Nominal Diameter (mm)	Product Details
1	Steel Strand, Un-Coated Seven-Wire for Prestressed Concrete	9.53	Seven-Wire Low relaxation steel strand No. 9, grade 1860[270] with nominal diameter 9.53mm, minimum Breaking Strength of 102.3 kN.
2	Steel Strand, Un-Coated Seven-Wire for Prestressed Concrete	12.7	Seven-Wire Low relaxation steel strand No. 13, grade 1860[270] with nominal diameter 12.7mm, minimum Breaking Strength of 183.7 kN.
3	Steel Strand, Un-Coated Seven-Wire for Prestressed Concrete	15.24	Seven-Wire Low relaxation steel strand No. 15, grade 1860[270] with nominal diameter 15.24mm, minimum Breaking Strength of 260.7 kN.

NOTE: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

Original Issue Date : 07th April 2009
Current Issue Date : 07th April 2011
Valid Until : 06th April 2012



ENGR. AMIN AHMED MOHAMMED AMIN
Head of Inspection and Certification Section
Dubai Central Laboratory Department

Handwritten initials in the bottom left corner.