



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality,
hereby attests that the product(s):

FACTORY-MADE RIGID POLYISOCYANURATE FOAM
(Details as per the attached Scope of Certification)

manufactured by:

GULF COOL THERM FACTORY LTD.

P.O. Box 22069, Sharjah, UAE

have been assessed in accordance with DCLD Document Ref. No. RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13165:2008

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark to the above-mentioned product(s).


ENGR. HAWA ABDULLA BASTAKI
Director, Dubai Central Laboratory Department
Dubai Municipality

Certificate No: CL10020127
Valid Until: 22 March 2013

Current Issue Date: 23 March 2012
Original Issue Date: 23 March 2010



CB-003



The attached Scope of Certification bearing the same Certificate No. forms an integral part of this certificate.
This certificate is subject to the Terms and Conditions of the Product Certification System



**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL10020127**

Certificate Issued To:	GULF COOL THERM FACTORY LTD. P.O. Box 22069 Sharjah UAE
Applicable Standard Specification:	BS EN 13165:2008 –Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products - Specification
Applicable Specific Rules:	RD-DP21-2124 (IC) “Specific Rules for Certification of Factory Made Rigid Polyurethane Foam (PUR) Thermal Insulation Products (as per BS EN 13165:2008) Through Factory Assessment”.

S/N	Product Description	Brand Name	Product Details
1	Factory made rigid polyisocyanurate (PIR) foam	Gulf Cool Therm	PIR 35 Insulation Foam Nominal Thickness - 20 mm ~ 100 mm ; Nominal Length 1000 mm ~ 2440 mm; Nominal Width 1000 mm ~ 1220 mm; Apparent Density 32 kg/m ³ (min); Reaction to fire Class E; Thermal conductivity - 0.030 W/(m*K) @ 35C & aged value – 0.034 W/(m*K) @ 35C ; Code: PIR-EN 13165-T1-DS(TH)1-CS(10/Y)100 Manufactured with aluminum foil facing on both sides to be used as thermal insulation materials.

NOTE 1: This certification covers only the PIR foam within the panel

- 2: This document forms part of the Certificate of Product Conformity bearing the same certificate number.
3. The above products shall bear the DCL Conformity Mark (applied on each product or on the packaging)

Original Issue Date : 23 March 2010
Current Issue Date : 23 March 2012
Valid Until : 22 March 2013

ARIF HUSAIN AL MARZOUQI
Acting Head of Inspection and Certification Section
Dubai Central Laboratory Department