



CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality,
hereby attests that the product(s):

FACTORY-MADE RIGID POLYURETHANE FOAM

(Details as per the attached Scope of Certification)

manufactured by:

RIGIDAL INDUSTRIES LLC

P.O. Box 60493 Dubai Investment Park, Dubai UAE

have been assessed in accordance with DCLD Document Ref. No. RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

BS EN 13165:2008

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark to the above-mentioned product(s).

ENGR. HAWA ABDULLA BASTAKI
Director, Dubai Central Laboratory Department
Dubai Municipality



Certificate No: CL06020026
Valid Until: 19 November 2012

Current Issue Date: 20 November 2011
Original Issue Date: 20 November 2006

The attached Scope of Certification bearing the same Certificate No. forms an integral part of this certificate.
This certificate is subject to the Terms and Conditions of the Product Certification System



CB-003

**DUBAI CENTRAL LABORATORY DEPARTMENT
DCL PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL06020026**

Certificate Issued To: RIGIDAL INDUSTRIES LLC
P.O. Box 60493 DIP, Dubai UAE

Applicable Standard Specification: BS EN 13165:2008 –Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products - Specification

Applicable Specific Rules: RD-DP21-2124 (IC) "Specific Rules for Certification of Factory Made Rigid Polyurethane Foam (PUR) Thermal Insulation Products (as per BS EN 13165:2008) Through Factory Assessment".


S/N	Product Description	Brand Name	Product Details
1	Factory made rigid polyurethane (PUR) & polyisocyanurate (PIR) foam	1. RIGIDAL THERMOCORE 2. RIGIDAL FORMAWALL1000H 3. RIGIDAL VERSACOR ULTIMA 4. RIGIDAL THERMAWALL	PUR/PIR Insulation Foam Nominal Thickness - 35 mm (min) for wall and 50 mm (min) for roof ; Nominal Length 12.5 m (max); Nominal Width – 999 mm (max); Apparent Density 35 kg/m ³ (min); Thermal conductivity - 0.025 W/(m*K) @35°C & 60% RH; Reaction to Fire: Meets Euro Class E Classification Code: PUR/PIR-EN 13165-T2-DS(TH)10-12-CS(10/Y)100 Manufactured with corrugated aluminum or Galvanized iron (GI) Sheet facing either on one side or both sides to be used as thermal insulation for sandwich panel.

NOTE 1: The above products shall bear the DCL Conformity Mark (applied on each product or on the packaging).

NOTE 2: This certification covers only the PUR/PIR foam within the panel

NOTE 3: This document forms part of the Certificate of Product Conformity bearing the same certificate number.

Original Issue Date : November 20, 2006
Current Issue Date : November 20, 2011
Valid Until : November 19, 2012


ENGR. AMIN AHMED MOHAMMED AMIN
Head of Inspection and Certification Section
Dubai Central Laboratory Department